



BAROMETER PRESSURE STANDARD PRESSURE CONTROLLER

903x NetScanner System

Models 9034 and 9038 are compact pressure calibrators with set-point control accuracy of up to $\pm 0.01\%$ FS that are also capable of extraneous pressure measurement. The calibrators provide a pre-engineered solution for applying known stable pressures to electronic pressure scanners, or any pressure measurement device, for periodic calibration or verification.

Model 9032 and 9033 are precision pressure standards capable of measuring dry non-corrosive gases to an accuracy of $\pm 0.01\%$ FS. The Model 9032 Barometer offers an excellent solution for precision measurement of atmospheric pressures to complement differential electronic pressure scanners used in the acquisition of multiple pressures.

Available in absolute and differential versions, both products also provide digital I/O for electronic control of remotely located valves for use in routing measurement and control pressures as desired.

The units communicate with the host computer via a 10 Base-T Ethernet interface supporting both TCP and UDP protocols. Pressure data is output in user-selectable engineering units. An internal 32-bit microprocessor in each unit corrects for zero, span and non-linearity errors of the internal precision pressure standard. It also performs digital temperature compensation of the standard to reduce thermal errors to less than $\pm 0.001\%$ FS/ $^{\circ}$ C.

The pressure standards and pressure controllers are components of the NetScanner System. Multiple NetScanner components measuring a variety of pressures and sharing the same command set can be networked to form a distributed intelligent data acquisition system.

Features

- ◆ $\pm 0.01\%$ FS Measurement & Control Accuracy
- ◆ $\pm 0.001\%$ / $^{\circ}$ C Thermal Stability
- ◆ Pressure Ranges from ± 1 psid to 1200 psia

Applications

- ◆ Barometric Measurement
- ◆ Pressure Scanner Verification Testing
- ◆ Pressure Scanner Span Calibration

BAROMETER PRESSURE STANDARD PRESSURE CONTROLLER

903x NetScanner System

Specifications

*After 1 hour warmup @ 25°C with atmospheric reference pressure unless otherwise stated / FS= Full Scale

PARAMETER	9032	9034	9033	9038	UNITS	COMMENTS
PNEUMATICS						
Reference Pressure Format	Absolute		Differential			
Pressure Range	11-16	100				
	15	200				
	23	300				
	30	500	±1		psi	
	45	750	±5			
	65	1200				
Media	Dry, non-corrosive gas					
Output Range ¹	N/A	5 to 100	N/A	-100 to 100	% FS	9038, see reference pressure
Source Gas ²	N/A	FS + 10	N/A	FS + 10	psi	range ≤ 100 psi
		1.1	N/A	N/A	x FS	range > 100 psi
	Min	250	N/A	250	psi	range ≤ 100 psi
Max	1.5	N/A	N/A	x FS	range > 100 psi	
Vacuum ³	N/A	2	N/A	2	scfm	
Output Flow Capacity	N/A	0.1	N/A	0.1	scfm	min
Overpressure ⁴ (input/output/ref ports)		1.3			x FS	max
STATIC PERFORMANCE						
Measurement Resolution	±0.0005		±0.003		% FS	
Relative Accuracy ⁵	±0.01		±0.03		% FS	
			±0.01		± 1 psid ± 5 psid	
Long Term Stability	±0.01		±0.05 ⁶		% FS/6 mos.	
Thermal Stability ⁷	±0.001				% FS/°C from 25°C	
Measurement Rate ⁸	10				readings/sec	
Controller Setpoint Resolution	N/A	0.003	N/A	0.003	% FS	

*Specifications subject to change without notice.

BAROMETER PRESSURE STANDARD PRESSURE CONTROLLER

903x NetScanner System

Specifications

*After 1 hour warmup @25 C with atmospheric reference pressure unless otherwise stated / FS= Full Scale

PARAMETER	9032	9034	9033	9038	UNITS	COMMENTS
ELECTRICAL						
Input Voltage		18 - 36			VDC	unregulated
Input Current		250 850			mA	@ 24 VDC, quiescent @ 24 VDC, active
Hardware Trigger Threshold		2.5			VDC	TTL compatible differential input, ±5 VDC common mode voltage
Digital Input/Output						
Output Voltage ⁹					VDC	max
Sink Current per Output		18-36 0.5			A	max
Max Source Current ¹⁰		1.0			A	max @ +24 VDC
COMMUNICATION						
Communication		10Base-T Ethernet			% FS	
Protocol		TCP and UDP			% FS	static or dynamic IP assignment
ENVIRONMENTAL/PHYSICAL						
Compensated Temp Range		0 to 50			°C	Contact factory for extended temperature range
		15 to 45			°C	range ≤ 5 psid
Operating Temp Range		-10 to 60			°C	Up to 95% non-condensing humidity
		0 to 50			°C	range ≤ 5 psid
Storage Temp		-20 to 80			°C	
		0 to 70			°C	range ≤ 5 psid
Size		9.5 x 3.5 x 3.875			inches	L x W x H, range < 750 psi
		9.5 x 6.375 x 3.85				L x W x H, range ≥ 750 psi range ≤ 5 psid
Weight	4.0	5.2	4.0	5.2	lb	range < 750 psi
	5.8	7.0	N/A	N/A	lb	range ≥ 750 psi
	N/A	N/A	7.4	8.6	lb	range ≤ 5 psid

Notes:

- Control of sub atmospheric pressures requires vacuum pump.
- Gas should be pre-filtered to 10 microns, free of oil and have dew point of -25°C.
- Required for control of sub atmospheric pressure, recommended for control near zero psig.
- For absolute reference units (9032 & 9034), overpressure is defined as the maximum absolute pressure which may be applied to the unit without damage. For differential units (9033 & 9038), overpressure is defined as the maximum pressure differential between the pressure standard input and reference.
- Relative accuracy includes the combined errors due to non-linearity, hysteresis and non-repeatability.
- After internal rezero
- Includes effects of zero and span.
- Measurement rate to host computer depends on host computer software throughput rate. Consult user's manual for more information.
- Output voltage directly equivalent to 903x input voltage supply.
- Maximum sink/source current for all external control outputs.


*Specifications subject to change without notice.

Pneumatics

9032

The absolute reference 9032 is designed to measure a single absolute pressure. The quartz standard is connected directly to the input port. The relief valve is set to vent at 110% of the instruments full scale pressure. The 9032 is most commonly used as a barometer, where the range is specifically calibrated for use at 11-16 psia.


9032 PRESSURE STANDARD



9033

The differential reference 9033 is designed to measure a single differential pressure. Normally the high side is connected to the input port while the low side would be connected to the reference input. The instrument is designed to measure differential pressure at a maximum common mode (line) pressure of 200 psia. The bi-directional relief valves vent if either input exceeds the other by 110% of the instrument's full scale pressure. The rezero solenoid allows the user to minimize zero error due to line pressure, temperature and drift with time on the pressure standard.


9033 PRESSURE STANDARD



9034

The absolute reference 9034 is designed to control pressure between 5%-100% of the instrument's full scale pressure range. A digitally controlled pneumatic servo valve modulates the mix of supply/vent pressure to its output allowing pressures to be controlled from near vacuum to the full scale of the instrument. A quartz pressure standard measures the servo valve output. The microprocessor adjusts this valve to set the requested pressure. The instrument may also be used in a measurement mode by applying the pressure to be measured at the output port. The pressure relief valve is designed to vent at 110% of the instrument's full scale pressure. The 750 psia unit does not contain a pressure relief valve.


9034 PRESSURE STANDARD



9038

The differential reference 9038 is designed to control pressures between vacuum and +100 % of the instrument's full scale pressure range. The instrument will control pressures at elevated reference (line) pressures. As an example, if the applied reference pressure was 10 psi and the requested control pressure was 5.0 psi, the instrument would output 15 psi on the output port. The pressure standard is designed for reference pressures within the calibrator's full scale of ambient pressure. The pressure standard is measured under microprocessor control to maintain the desired control pressure. The rezero solenoid allows the user to execute pneumatic rezero of the pressure standard on demand. The instrument may also be used in a measurement mode by applying the pressure to be measured to the output port. The instrument is protected by bi-directional relief valves designed to vent whenever either the output or reference port exceeds the other by 110% of the full scale pressure.

9038 PRESSURE STANDARD




Theory of Operation

Digital I/O

Digital I/O is available on the front panel for user applications. A software command allows each of the outputs, K1 - K4, to be independently set or reset. The open-collector output drivers can operate external Solenoids or external pull-up resistors can be connected to provide logic outputs. Up to 1A of 18-36 VDC power is available for external use. External solenoids requiring less than 0.5A may be directly connected to the I/O connector. The output current for each driver should not exceed 0.5A and the total current, for all four outputs, should not exceed 1A.

A software command is used to read the four digital inputs, D1 - D4. These inputs can be used to sense TTL signals or external pull-up resistors may be added to sense contact closures. Up to 50 V may be applied without damage.



External Digital I/O

Networking and Software

The 9032/9033/9034/9038 are part of a networked solution for pressure measurement and pressure control. These modules are networked via Ethernet 10 Base-T using commonly available networking hardware. Interface can be direct to a host computer using a standard Ethernet card, with MEAS networking hardware or via an appropriate local area network (LAN).

The internal microprocessor performs the more complex tasks like engineering unit calculation and pressure control. A standard command set allows the user to send simple commands to read pressures and set pressures.

READ PRESSURE

The 9032 and 9034 can be used to accurately measure an absolute pressure. Barometric pressure is the most common measurement pressure. The 9033 and 9038 can be used to accurately measure a differential pressure applied to the input ports of the unit. One simple command is sent to request current pressure readings. Data may be returned in several user selected output formats.

REZERO PRESSURE STANDARD

From time to time, the user may rezero the differential sensor of the 9033/9038 by commanding the unit to perform an on-line pneumatic rezero. This causes the instrument to shunt the sensor input and the reference sides together. The transducer is then read and the offset is used to remove any thermal or long term drift which has occurred since the calibration. The rezero term may be stored in instrument nonvolatile memory for later use.

SET PRESSURE


The 9034 and 9038 may be used to accurately control a pressure by one or more commands. Single point pressures may be generated by a single command. A sequence of pressures may be generated which the user has stored within the instrument. The 9034/9038 can automatically set a predefined sequence of pressures, holding each set point for a user defined period of time. The instrument may also advance through the sequence of pressures in response to host computer commands.

BAROMETER PRESSURE STANDARD PRESSURE CONTROLLER

903x NetScanner System

Front Panel Layout

The instrument's front panel contains all pneumatic and electrical connections necessary to operate the device. The unit is supplied with standard English or optional metric pneumatic fittings. Mating electrical connector or combined networking/power/trigger cables are specified separately. Maximum cable length is 328ft (100m).




BAROMETER PRESSURE STANDARD PRESSURE CONTROLLER


903x NetScanner System

Pneumatic/Electrical Interface Example

This example depicts the electrical/pneumatic connection and required cables and support equipment necessary to interface a 9038 to a host computer. Shop air may be used for the supply if it is free of moisture, oil and contaminants.



Dimensions



No. 0808

BAROMETER PRESSURE STANDARD PRESSURE CONTROLLER

903x NetScanner System

Ordering/Part Number Information

Ordering Information:

PN: **9032-9900CC0300** Barometer, 11-16 psia

CC = Fitting

01, 1/4" Compression Fitting 03, 4mm Compression Fitting
02, 1/8" Compression Fitting 04, 6mm Compression Fitting

PN: **9032-AA00CC0300** Pressure Standard, Absolute
9034-AA00CC0300 Pressure Controller, Absolute

AA = Pressure Range

01, 15 psia	03, 30 psia	65, 65 psia
10, 100 psia	30, 300 psia	75, 750 psia
23, 23 psia	45, 45 psia	12, 1200 psia
20, 200 psia	50, 500 psia	

CC = Pneumatic Connection

01, 1/4" Compression Fittings
02, 1/8" Compression Fittings
03, 4mm Compression Fittings
04, 6mm Compression Fittings

D = Case Size

0, Single width, standard
1, Double width, required for 750 & 1200 psia

PN: **9033-AA00CCD300** Pressure Standard, Differential, Ethernet
9038-AA00CCD300 Pressure Controller, Differential, Ethernet

AA = Pressure Range

01, ±1 psid
05, ±5 psid

CC = Pneumatic Connection

01, 1/4" Compression Fittings
02, 1/8" Compression Fittings
03, 4mm Compression Fittings
04, 6mm Compression Fittings

D = Case Size

0, Single width, standard
1, Double width, required for 1 and 5 psid

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

中国大陆
西安鑫源宇通电子科技有限公司
陕西省西安市高新区锦业路70号航
天恒星园区1号厂房一层南
Tel: 400-780-9688
sales@senstechxyz.com

中国香港
深大实业有限公司
香港新界沙田安平街6号新贸易
中心B座13楼06室
Tel: +86 17792099916
info@caltropinstruments.com

新加坡
深大实业有限公司
香港新界沙田安平街6号新贸易
中心B座13楼06室
Tel: +86 17792099919
info@senstechxyz.com