



FS-90/1 FS Series Flow Sensor

Features

- Rugged high grade Noryl
- Minimum pressure drop
- Operates from a small head of water
- Mount in any axis
- Suitable for water and air flow switching

Comments

- 15mm copper pipe
- · Suitable for hot and cold potable water
- Reed Switch Reliability File E125629
- Meets UL 94-HB flammability rating
- Food grade material

Applications

- Leak detection
- Flow sensing
- Mains water control
- Cooling systems •
- Circulation pump protection



Maximum Pressure

Switch On Flow Rate L/min

Switch Action (Reed Switch)

Max Switching Voltage VDC

Max Switching Voltage VAC

Max Switching Load Watt

Max Switching Current Amps

ID

Switching

Operate Mode

Contact Form

Connection Type

Cable Type

Mounting Fitting

Fitment Mounting

Cable Colour

Cable **Cable Length**

Material

Technical Drawing Housing Material Brass Shuttle Material Noryl FS-90/1 15mm Copper Spring Material Stainless Steel Pipe to EN1057-R250 40 R 4.50 13.20 **Contact Material** Ruthenium (0.52) (1.57) (0.18) -30 to 85 **Operating Temperature °C** Medium Water 12 **Housing Colour** Black 39.70 73 **Mechanical Specifications** Flow Direction (1.56) Shock 50g For A 11ms Duration 152.40 (6.00) Vibration 35g up tp 500Hz

10 Bar @ 20ºC

N/O, Close With Flow

2 x 1.0M single insulated

16/0.2mm PVC insulated

Stripped Cables

Black/Black

15mm Plain In Line

Any Axis

IP65

3.0

SPST

200

250

1

40

А

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the roduct. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

中国大陆 西安鑫源宇通电子科技有限公司

陕西省西安市高新区科技六路西段 西安国家数字出版基地A栋12402 Tel: 400-780-9688 sales@senstechxyz.com

中国香港 深大实业有限公司 香港新界沙田安平街6号新贸易 中心B座13楼06室 Tel:+86 17792099916 info@caltropinstruments.com

新加坡 深大实业有限公司 香港新界沙田安平街6号新贸易 中心B座13楼06室 Tel:+86 17792099919 info@senstechxyz.com

POSITION SENSOR /// FS-90/1

11/2016



蠹源宇通 西安鑫源宇通电子科技有限公司 | 400-780-9688 | www.senstechxyz.com